

eMH3 WALLBOX SINGLE

WITH CHARGING CABLE

22 kW

Our new eMH3 wallbox impresses with an extremely clean and elegant design. The color backlit symbols in the mirror-finish black cover with silver frame indicate the current charging status. This eMH3 Single has a fixed charging cable with a Type 2 coupler and a charging capacity of up to 22 kW. For access control, the internal RFID module of the eMH3 Wallbox can be activated at any time via software. The eMH3 comes with our own DC fault current detection installed as standard.



General information

Model	eMH3
Part number	3W2205
EAN number	4011721171470
Commodity code	85371091
Packaging unit (PU)	1 unit
Packaging (dimensions HxWxD)	492 x 400 x 194 mm
Includes	eMH3 Wallbox, printed Quick Start Guide, 1 three-square socket wrench

Input/Supply

Power supply	for supply cable sizes up to 5 x 10 mm ²
Rated voltage	230 / 400 V
Rated current	32 A
Rated frequency	50 Hz
Back-up fuse	32 A (required onsite), C characteristic recommended
Terminal block	Direct connection to RCCB PE: 10 mm ² feed-through terminal block

Output/vehicle connection

Connection system	Single charging cable with Type 2 connector in acc. with IEC62196-2, approx. 6 m
Output voltage	230 / 400 V
Max. charging current	32 A
Maximum output	22 kW
Shut down (Standby)	all contacts

Protection/integrated components

RCCB	RCCB, Type A, 30 mA
DC fault current detection	electronic, $I_{\Delta n \text{ d.c.}} \geq 6 \text{ mA}$
Energy meter	-
Installation contactor	4-pole (charging procedure activation)

Charge control/status indicators

Communication	in acc. with IEC 61851-1, Mode 3
Operating status indicator	LED (stand-by, EV detected, charging)
Firmware indicator	LED (flashes on startup)
Fault indicator	LED (various flash patterns)
Interface	RS485
RFID card reader	integrated (disabled by default), support for MIFARE ULTRA-LIGHT transponder
Access control	RFID (after activation via software tool)

Standards/Directives

IEC 61851-1 / 61439-7

Operating conditions

Storage temperature	-30°C to 85°C
Operating temperature	-30°C to 50°C
Relative humidity	5 to 95%, no condensation
Class of protection	I
Overvoltage category	III
Pollution degree	3
Degree of protection (housing)	IP54
Power dissipation	0.5 W

Housing

Type	Wall-mounted housing
Fixing type	Wall mounting via supplied mounting plate and screws
Material (housing)	Plastic
Housing color	RAL9005, black
Material (door)	Plastic
Door color	RAL9005, black
Locking mechanism	integrated lock
Dimensions (HxWxD)	492 x 400 x 192 mm
Weight	ca. 13 kg

Optional accessories

Pole	STEMH30
------	---------

Dimensioned drawing

