

D51SL30

CEE wall socket
16A · 5p · 400V · 6h · red

- Housing material: PA6
- Nominal current: 16 A
- Number of poles: 5 (3P+N+PE)
- Clock position: 6 h
- Rated voltage/frequency: 200/346V~ – 240/415V~ / 50+60Hz
- Contacts: Brass
- Connection technology: Screwless terminals (TT)
- Cable entry: Top and rear incl. threaded cable grommet
- Protection degree: IP44



Design may vary

GENERAL

Model	CEE wall socket, 16A
Product number	D51SL30
EAN number	9003399622571
Commodity code	85366990
Net weight product	0.260 kg
Packaging unit (PU)	10 units
Coding colour	Red

ELECTRICAL PARAMETERS

IEC amperage	16 A
Voltage according to EN 60309-2	400 V (50+60 Hz) red
Number of poles	5
Clock position	6 h

OPERATING CONDITIONS

Ambient temperature	-25 – 40 °C
Temperature resistance	-25 – 80 °C
IP rating	IP44

MATERIALS

Contact material	CuZn
Surface treatment contacts	Untreated
Housing material	Plastic

CONNECTION

Construction	Surface mounted
Fixing type	Internal mounting
Connection system	Screwless terminal
Cable entry	Gland nut
Housing screws	110 Ncm
Wire flexible	1 – 2.5 mm ²
Wire solid	1 – 4 mm ²
Jacket stripping length	50 mm
Insulation stripping length	10 – 12 mm



Height = 104mm

