

D53S36

CEE wall socket
63A · 5p · 400V · 6h · red

- Housing material: PC/ABS
- Nominal current: 63 A
- Number of poles: 5 (3P+N+PE)
- Clock position: 6 h
- Rated voltage/frequency: 200/346V~ – 240/415V~ / 50+60Hz
- Contacts: Brass, with lamellar spring (CuBe)
- Connection system: Frame terminals with screws
- Cable entry: Top, bottom, rear (housing can be rotated 180°) incl. threaded blind cap
- Protection degree: IP66/IP67



Design may vary

GENERAL

Model	CEE wall socket, 63A
Product number	D53S36
EAN number	9003399135064
Commodity code	85366990
Net weight product	0.923 kg
Packaging unit (PU)	1 unit
Coding colour	Red

ELECTRICAL PARAMETERS

IEC amperage	63 A
Voltage according to EN 60309-2	400 V (50+60 Hz) red
Number of poles	5
Clock position	6 h

OPERATING CONDITIONS

Ambient temperature	-25 – 40 °C
Temperature resistance	-25 – 80 °C
IP rating	IP67

MATERIALS


Contact material	CuZn
Surface treatment contacts	Untreated
Housing material	Plastic

CONNECTION

Construction	Surface mounted
Fixing type	External mounting
Insulated mounting	Yes
Military model	No
Connection system	Screwed terminal
Cable entry	Gland nut
Contact screws	200 Ncm
Housing screws	200 Ncm
Wire flexible	6 – 16 mm ²
Wire solid	6 – 25 mm ²
Jacket stripping length	100 mm
Insulation stripping length	15 – 18 mm



PRODUCT DIMENSIONS



Height: 173 mm

Subject to change: All performance characteristics, technical and other specifications are subject to change without prior notice.