

G53S35

CEE wall-mounted plug
63A · 5p · 400V · 6h · red

- Housing material: PC/ABS
- Nominal current: 63 A
- Number of poles: 5 (3P+N+PE)
- Clock position: 6 h
- Rated voltage/frequency: 200/346V~ – 240/415V~ / 50+60Hz
- Contacts: Brass nickel plated, with pilot pin
- Connection system: Frame terminals with screws
- Protection degree: IP66/IP67



Design may vary

GENERAL

Model	CEE wall-mounted plug, 63A
Product number	G53S35
EAN number	9003399068003
Commodity code	85366990
Net weight product	0.914 kg
Packaging unit (PU)	1 unit
Coding colour	Red

ELECTRICAL PARAMETERS

IEC amperage	63 A
Voltage according to EN 60309-2	400 V (50+60 Hz) red
Number of poles	5
Clock position	6 h

OPERATING CONDITIONS

Ambient temperature	-25 – 40 °C
Temperature resistance	-25 – 80 °C
IP rating	IP67

MATERIALS

Contact material	CuZn
Surface treatment contacts	Nickel plated
Housing material	Plastic

CONNECTION

Construction type	Surface mounted device plug
Connection system	Screwed terminal
Contact screws	200 Ncm
Housing screws	200 Ncm
Connecting screws	200 Ncm
Angle of plug	Angled (15°)
Wire flexible	6 – 16 mm ²
Wire solid	6 – 25 mm ²
Jacket stripping length	100 mm
Insulation stripping length	15 – 18 mm
IK code *	IK08

* The IK-test is not part of the IEC 60309 standard for industrial plugs and socket-outlets or the IEC 60884 standard for household plugs and socket-outlets. Therefore, the IK codes of these products were determined in accordance with IEC 62262 and according to the test procedure of IEC 60068-2-75 Ehc, with conditioning for 48 hours at 40 °C and a relative humidity of 95%.



Height: 175 mm

