

S42S30

CEE plug straight
32A · 4p · 400V · 6h · red



- Housing material: PA6
- Nominal current: 32 A
- Number of poles: 4 (3P+PE)
- Clock position: 6 h
- Rated voltage/frequency: 380–415V~ / 50+60Hz
- Contacts: Brass
- Connection system: Screwed terminals
- Protection degree: IP44/IP54

Design may vary

GENERAL

Model	CEE plug straight, 32A
Product number	S42S30
EAN number	9003399136320
Commodity code	85366990
Net weight product	0.201 kg
Packaging unit (PU)	10 units
Coding colour	Red

ELECTRICAL PARAMETERS

IEC amperage	32 A
Voltage according to EN 60309-2	400 V (50+60 Hz) red
Number of poles	4
Clock position	6 h

OPERATING CONDITIONS

Ambient temperature	-25 – 40 °C
Temperature resistance	-25 – 80 °C
IP rating	IP44

MATERIALS

Contact material	CuZn
Surface treatment contacts	Untreated
Housing material	Plastic


CONNECTION

Connection system	Screwed terminal
Cable entry	Gland nut
Contact screws	110 Ncm
Angle of plug	Straight
Wire flexible	2.5 – 6 mm ²
Cable diameter	11.5 – 20 mm
Jacket stripping length	50 mm
Insulation stripping length	12 – 14 mm
Strain relief	600 Ncm
IK code *	IK10

* The IK-test is not part of the IEC 60309 standard for industrial plugs and socket-outlets or the IEC 60884 standard for household plugs and socket-outlets. Therefore, the IK codes of these products were determined in accordance with IEC 62262 and according to the test procedure of IEC 60068-2-75 Ehc, with conditioning for 48 hours at 40 °C and a relative humidity of 95%.



PRODUCT DIMENSIONS



Subject to change: All performance characteristics, technical and other specifications are subject to change without prior notice.